

BLUESTAR OPTO LIMITED

Professional LED Display Manufacturer & Export Supplier

LED Display Product Catalog

P2.6 · P2.9 · P3.91 · P5 · P8 · P10

Indoor · Rental · Outdoor · Custom

Featured products only · We manufacture any model on demand

September 2026

www.bluestaroptolimited.com

Contents

Company Profile	3
Selection Guide	4
Indoor LED Video Wall · 6 models	5
Outdoor LED Display · 6 models	12
Outdoor Large-Format LED Display · 5 models	19
LED Poster Display · 1 model	25
Specification Comparison	27-28
How to Order · Contact	29

This catalog presents only our featured products. Our factory can manufacture LED displays of any model and customize all parameters to your requirements.

Bluestar Opto Limited

Bluestar Opto Limited is a professional LED display manufacturer and export supplier, serving outdoor advertising, stage rental, retail, shopping malls, control rooms and customized commercial projects worldwide.

From pixel pitch selection to cabinet design, aging test and export packing, every screen is inspected before shipment. Send your screen size and application for a fast, practical quotation.

This catalog presents only our featured products. Our factory can manufacture LED displays of any model and customize all parameters to your requirements.

Why Bluestar

- Factory direct supply — competitive factory pricing configured to your viewing distance, environment and budget.
- Professional QC before shipment — module inspection, cabinet assembly testing, aging test and final screen verification.
- Fast quotation — send screen size, application and destination country for a fast, practical proposal.
- Global export experience — export packing, shipping support and remote technical guidance.
- OEM & ODM customization — cabinet size, pixel pitch, logo, packaging and project solutions.
- Certifications — CE, RoHS and FCC documents available per project requirements.

Quality Control Process



Choose the Right LED Screen

Start with where the screen will be used, how close people will view it, and whether it is fixed or rental.

Model	Best Use	Viewing Distance	Recommended Projects
P2.6	Indoor HD video wall	2.6m – 9m	Retail stores, showrooms, meeting rooms, control rooms
P2.9	Indoor commercial display	2.9m – 9m	Shopping malls, brand displays, conference rooms
P3.91	Rental stage / events	3.9m – 12m	Concerts, exhibitions, stage backgrounds
P5	Outdoor billboard	5m – 15m	Roadside advertising, building façades, commercial plazas
P8	Outdoor billboard	8m – 80m	Highways, roads, building façades, long-distance advertising
P10	Outdoor billboard	10m – 100m	Highways, stadiums, large billboards

Quotation checklist: screen width × height · indoor / outdoor · fixed / rental · viewing distance · destination country · preferred pixel pitch

PRODUCT LINE

Indoor LED Video Wall

Fine-pitch screens for close viewing — retail, malls, meeting rooms and stage backdrops.

P2.6 500X1000mm Indoor

P2.6 500X500mm Indoor

P2.9 500X1000mm Indoor

P2.9 500X500mm Indoor

P3.91 500X1000mm Indoor

P3.91 500X500mm Indoor

P2.6 500X1000mm Indoor

Best for: retail stores, showrooms, meeting rooms and close-view indoor video walls



2.6mm fine-pitch indoor HD display with sharp close-view image quality — ideal for retail, showrooms, meetings and stage backdrops where clarity matters. Cabinet size, pixel pitch, logo, packaging and full project solutions can be customized.

Model P2.604	Pixel Pitch 2.604mm	LED Type SMD1515
Pixel Configuration 1R1G1B	Module Size 250mm×250mm	Module Resolution 96×96 pixels
Cabinet Size 500mm×1000mm	Cabinet Resolution 192×384 pixels	Cabinet Material Die-cast aluminum
Brightness ≥1000CD/m²	Refresh Rate ≥7680Hz	Gray Scale 16 bit
Viewing Angle 140°/140°	Optimal Viewing Distance 2.6m – 9m	Scan Method 1/32
IP Rating IP45 (indoor)	Power Consumption 850W/sqm (max) · 350W/sqm (avg)	Cabinet Weight 15 kgs

Pixel Density: 147,456 dots/sqm · Cabinet Thickness: 80mm · Driver IC: FM6373 · Color Temperature: 6,500K · Lifespan: 100,000 hours · Working Voltage: AC 100/240V 50-60Hz · MOQ: 6 sqm · EXW Price: contact for quotation

P2.6 500X500mm Indoor

Best for: retail stores, showrooms, meeting rooms and close-view indoor video walls



Compact 500×500mm cabinet version for flexible small-area and creative splicing, with the same 2.6mm HD quality and ≥7680Hz refresh rate.

Model P2.604	Pixel Pitch 2.604mm	LED Type SMD1515
Pixel Configuration 1R1G1B	Module Size 250mm×250mm	Module Resolution 96×96 pixels
Cabinet Size 500mm×500mm	Cabinet Resolution 192×192 pixels	Cabinet Material Die-cast aluminum
Brightness ≥1000CD/m²	Refresh Rate ≥7680Hz	Gray Scale 16 bit
Viewing Angle 140°/140°	Optimal Viewing Distance 2.6m – 9m	Scan Method 1/32
IP Rating IP45 (indoor)	Power Consumption 850W/sqm (max) · 350W/sqm (avg)	Cabinet Weight 7.5 kgs

Pixel Density: 147,456 dots/sqm · Cabinet Thickness: 80mm · Driver IC: FM6373 · Color Temperature: 6,500K · Lifespan: 100,000 hours · Working Voltage: AC 100/240V 50-60Hz · MOQ: 6 sqm · EXW Price: contact for quotation

P2.9 500X1000mm Indoor

Best for: shopping malls, brand displays, meeting rooms and commercial interiors



2.9mm indoor commercial display balancing clarity and cost — a popular choice for shopping malls, brand zones and meeting rooms.

Model P2.976	Pixel Pitch 2.976mm	LED Type SMD1515
Pixel Configuration 1R1G1B	Module Size 250mm×250mm	Module Resolution 84×84 pixels
Cabinet Size 500mm×1000mm	Cabinet Resolution 168×336 pixels	Cabinet Material Die-cast aluminum
Brightness ≥1000CD/m²	Refresh Rate ≥7680Hz	Gray Scale 16 bit
Viewing Angle 140°/140°	Optimal Viewing Distance 2.9m – 9m	Scan Method 1/28
IP Rating IP45 (indoor)	Power Consumption 850W/sqm (max) · 350W/sqm (avg)	Cabinet Weight 15 kgs

Pixel Density: 112,896 dots/sqm · Cabinet Thickness: 80mm · Driver IC: FM6373 · Color Temperature: 6,500K · Lifespan: 100,000 hours · Working Voltage: AC 100/240V 50-60Hz · MOQ: 6 sqm · EXW Price: contact for quotation

P2.9 500X500mm Indoor

Best for: shopping malls, brand displays, meeting rooms and commercial interiors



Compact 500×500mm cabinet for flexible splicing and small-space installation, with the same image quality as the large cabinet.

Model P2.976	Pixel Pitch 2.976mm	LED Type SMD1515
Pixel Configuration 1R1G1B	Module Size 250mm×250mm	Module Resolution 84×84 pixels
Cabinet Size 500mm×500mm	Cabinet Resolution 168×168 pixels	Cabinet Material Die-cast aluminum
Brightness ≥1000CD/m²	Refresh Rate ≥7680Hz	Gray Scale 16 bit
Viewing Angle 140°/140°	Optimal Viewing Distance 2.9m – 9m	Scan Method 1/28
IP Rating IP45 (indoor)	Power Consumption 850W/sqm (max) · 350W/sqm (avg)	Cabinet Weight 7.5 kgs

Pixel Density: 112,896 dots/sqm · Cabinet Thickness: 80mm · Driver IC: FM6373 · Color Temperature: 6,500K · Lifespan: 100,000 hours · Working Voltage: AC 100/240V 50-60Hz · MOQ: 6 sqm · EXW Price: contact for quotation

P3.91 500X1000mm Indoor

Best for: events, concerts, exhibitions and temporary stage backgrounds



3.91mm indoor rental stage screen with lightweight die-cast cabinets and quick locks for fast setup; high refresh rate keeps live and broadcast images smooth.

Model P3.91	Pixel Pitch 3.91mm	LED Type SMD2121
Pixel Configuration 1R1G1B	Module Size 250mm×250mm	Module Resolution 64×64 pixels
Cabinet Size 500mm×1000mm	Cabinet Resolution 128×256 pixels	Cabinet Material Die-cast aluminum
Brightness ≥1000CD/m²	Refresh Rate ≥7680Hz	Gray Scale 16 bit
Viewing Angle 140°/140°	Optimal Viewing Distance 3.9m – 12m	Scan Method 1/16
IP Rating IP45 (indoor)	Power Consumption 850W/sqm (max) · 350W/sqm (avg)	Cabinet Weight 15 kgs

Pixel Density: 65,536 dots/sqm · Cabinet Thickness: 80mm · Driver IC: FM6373 · Color Temperature: 6,500K · Lifespan: 100,000 hours · Working Voltage: AC 100/240V 50-60Hz · MOQ: 6 sqm · EXW Price: contact for quotation

P3.91 500X500mm Indoor

Best for: events, concerts, exhibitions and temporary stage backgrounds



Square 500×500mm cabinet version for creative shapes and curved splicing — a flexible choice for rental events.

Model P3.91	Pixel Pitch 3.91mm	LED Type SMD2121
Pixel Configuration 1R1G1B	Module Size 250mm×250mm	Module Resolution 64×64 pixels
Cabinet Size 500mm×500mm	Cabinet Resolution 128×128 pixels	Cabinet Material Die-cast aluminum
Brightness ≥1000CD/m²	Refresh Rate ≥7680Hz	Gray Scale 16 bit
Viewing Angle 140°/140°	Optimal Viewing Distance 3.9m – 12m	Scan Method 1/16
IP Rating IP45 (indoor)	Power Consumption 850W/sqm (max) · 350W/sqm (avg)	Cabinet Weight 7.5 kgs

Pixel Density: 65,536 dots/sqm · Cabinet Thickness: 80mm · Driver IC: FM6373 · Color Temperature: 6,500K · Lifespan: 100,000 hours · Working Voltage: AC 100/240V 50-60Hz · MOQ: 6 sqm · EXW Price: contact for quotation

PRODUCT LINE

Outdoor LED Display

High-brightness IP65 die-cast cabinets for outdoor advertising, façades and events.

P2.6 500X1000mm Outdoor

P2.6 500X500mm Outdoor

P2.9 500X1000mm Outdoor

P2.9 500X500mm Outdoor

P3.91 500X1000mm Outdoor

P3.91 500X500mm Outdoor

P2.6 500X1000mm Outdoor

Best for: outdoor advertising, events, commercial façades and DOOH projects



Outdoor fine-pitch HD screen with $\geq 5000\text{CD/m}^2$ brightness for clear daylight visibility and IP65 protection — for premium outdoor advertising and façade projects.

Model P2.604	Pixel Pitch 2.604mm	LED Type SMD1415
Pixel Configuration 1R1G1B	Module Size 250mm×250mm	Module Resolution 96×96 pixels
Cabinet Size 500mm×1000mm	Cabinet Resolution 192×384 pixels	Cabinet Material Die-cast aluminum
Brightness $\geq 5000\text{CD/m}^2$	Refresh Rate $\geq 7680\text{Hz}$	Gray Scale 16 bit
Viewing Angle 140°/140°	Optimal Viewing Distance 2.6m – 9m	Scan Method 1/32
IP Rating IP65 (outdoor)	Power Consumption 850W/sqm (max) · 350W/sqm (avg)	Cabinet Weight 15 kgs

Pixel Density: 147,456 dots/sqm · Cabinet Thickness: 80mm · Driver IC: FM6373 · Color Temperature: 6,500K · Lifespan: 100,000 hours · Working Voltage: AC 100/240V 50-60Hz · MOQ: 6 sqm · EXW Price: contact for quotation

P2.6 500X500mm Outdoor

Best for: outdoor advertising, events, commercial façades and DOOH projects



Compact 500×500mm cabinet for flexible outdoor small-area and custom installations, with the same high brightness and protection.

Model P2.604	Pixel Pitch 2.604mm	LED Type SMD1415
Pixel Configuration 1R1G1B	Module Size 250mm×250mm	Module Resolution 96×96 pixels
Cabinet Size 500mm×500mm	Cabinet Resolution 192×192 pixels	Cabinet Material Die-cast aluminum
Brightness ≥5000CD/m²	Refresh Rate ≥7680Hz	Gray Scale 16 bit
Viewing Angle 140°/140°	Optimal Viewing Distance 2.6m – 9m	Scan Method 1/32
IP Rating IP65 (outdoor)	Power Consumption 850W/sqm (max) · 350W/sqm (avg)	Cabinet Weight 15 kgs

Pixel Density: 147,456 dots/sqm · Cabinet Thickness: 80mm · Driver IC: FM6373 · Color Temperature: 6,500K · Lifespan: 100,000 hours · Working Voltage: AC 100/240V 50-60Hz · MOQ: 6 sqm · EXW Price: contact for quotation

P2.9 500X1000mm Outdoor

Best for: outdoor advertising, events, commercial façades and DOOH projects



2.9mm outdoor HD screen balancing image quality, brightness and cost — a workhorse for outdoor commercial display.

Model P2.976	Pixel Pitch 2.976mm	LED Type SMD1415
Pixel Configuration 1R1G1B	Module Size 250mm×250mm	Module Resolution 84×84 pixels
Cabinet Size 500mm×1000mm	Cabinet Resolution 168×336 pixels	Cabinet Material Die-cast aluminum
Brightness ≥5000CD/m²	Refresh Rate ≥7680Hz	Gray Scale 16 bit
Viewing Angle 140°/140°	Optimal Viewing Distance 2.9m – 9m	Scan Method 1/28
IP Rating IP65 (outdoor)	Power Consumption 850W/sqm (max) · 350W/sqm (avg)	Cabinet Weight 15 kgs

Pixel Density: 112,896 dots/sqm · Cabinet Thickness: 80mm · Driver IC: FM6373 · Color Temperature: 6,500K · Lifespan: 100,000 hours · Working Voltage: AC 100/240V 50-60Hz · MOQ: 6 sqm · EXW Price: contact for quotation

P2.9 500X500mm Outdoor

Best for: outdoor advertising, events, commercial façades and DOOH projects



Compact 500×500mm cabinet for flexible outdoor splicing and maintenance.

Model P2.976	Pixel Pitch 2.976mm	LED Type SMD1415
Pixel Configuration 1R1G1B	Module Size 250mm×250mm	Module Resolution 84×84 pixels
Cabinet Size 500mm×500mm	Cabinet Resolution 168×168 pixels	Cabinet Material Die-cast aluminum
Brightness ≥5000CD/m²	Refresh Rate ≥7680Hz	Gray Scale 16 bit
Viewing Angle 140°/140°	Optimal Viewing Distance 2.9m – 9m	Scan Method 1/28
IP Rating IP65 (outdoor)	Power Consumption 850W/sqm (max) · 350W/sqm (avg)	Cabinet Weight 7.5 kgs

Pixel Density: 112,896 dots/sqm · Cabinet Thickness: 80mm · Driver IC: FM6373 · Color Temperature: 6,500K · Lifespan: 100,000 hours · Working Voltage: AC 100/240V 50-60Hz · MOQ: 6 sqm · EXW Price: contact for quotation

P3.91 500X1000mm Outdoor

Best for: outdoor events, rental stages, commercial advertising and temporary installations



Outdoor rental/event screen with high brightness and refresh rate; quick-lock design for fast touring and temporary setups.

Model P3.91	Pixel Pitch 3.91mm	LED Type SMD1921
Pixel Configuration 1R1G1B	Module Size 250mm×250mm	Module Resolution 64×64 pixels
Cabinet Size 500mm×1000mm	Cabinet Resolution 128×256 pixels	Cabinet Material Die-cast aluminum
Brightness ≥5000CD/m²	Refresh Rate ≥7680Hz	Gray Scale 16 bit
Viewing Angle 140°/140°	Optimal Viewing Distance 3.9m – 12m	Scan Method 1/16
IP Rating IP65 (outdoor)	Power Consumption 850W/sqm (max) · 350W/sqm (avg)	Cabinet Weight 15 kgs

Pixel Density: 65,536 dots/sqm · Cabinet Thickness: 80mm · Driver IC: FM6373 · Color Temperature: 6,500K · Lifespan: 100,000 hours · Working Voltage: AC 100/240V 50-60Hz · MOQ: 6 sqm · EXW Price: contact for quotation

P3.91 500X500mm Outdoor

Best for: outdoor events, rental stages, commercial advertising and temporary installations



Square 500×500mm cabinet for outdoor creative shapes and curved stage builds.

Model P3.91	Pixel Pitch 3.91mm	LED Type SMD1921
Pixel Configuration 1R1G1B	Module Size 250mm×250mm	Module Resolution 64×64 pixels
Cabinet Size 500mm×500mm	Cabinet Resolution 128×128 pixels	Cabinet Material Die-cast aluminum
Brightness ≥5000CD/m²	Refresh Rate ≥7680Hz	Gray Scale 16 bit
Viewing Angle 140°/140°	Optimal Viewing Distance 3.9m – 12m	Scan Method 1/16
IP Rating IP65 (outdoor)	Power Consumption 850W/sqm (max) · 350W/sqm (avg)	Cabinet Weight 7.5 kgs

Pixel Density: 65,536 dots/sqm · Cabinet Thickness: 80mm · Driver IC: FM6373 · Color Temperature: 6,500K · Lifespan: 100,000 hours · Working Voltage: AC 100/240V 50-60Hz · MOQ: 6 sqm · EXW Price: contact for quotation

PRODUCT LINE

Outdoor Large-Format LED Display

Large-format P5 / P8 / P10 cabinets with excellent value for long-distance outdoor advertising.

P5 960X960mm Outdoor

P5 960X960mm Outdoor Fixed Installation (Iron Cabinet)

P5 640X640mm Outdoor

P8 960X960mm Outdoor

P10 960X960mm Outdoor

P5 960X960mm Outdoor

Best for: outdoor billboards, roadside advertising, building façades and long-distance viewing



P5 outdoor advertising screen with 960×960mm large cabinets for fewer seams — a cost-effective choice for long-distance viewing: roadside billboards, building façades and commercial plazas.

Model P5	Pixel Pitch 5mm	LED Type SMD1921
Pixel Configuration 1R1G1B	Module Size 320mm×160mm	Module Resolution 64×32 pixels
Cabinet Size 960mm×960mm	Cabinet Resolution 192×192 pixels	Cabinet Material Die-cast aluminum
Brightness ≥5000CD/m²	Refresh Rate ≥7680Hz	Gray Scale 16 bit
Viewing Angle 140°/140°	Optimal Viewing Distance 5m – 15m	Scan Method 1/8
IP Rating IP65 (outdoor)	Power Consumption 850W/sqm (max) · 350W/sqm (avg)	Cabinet Weight 28 kgs

Pixel Density: 40,000 dots/sqm · Cabinet Thickness: 80mm · Driver IC: FM6373 · Color Temperature: 6,500K · Lifespan: 100,000 hours · Working Voltage: AC 100/240V 50-60Hz · MOQ: 6 sqm · EXW Price: contact for quotation

P5 960X960mm Outdoor Fixed Installation (Iron Cabinet)

Best for: permanent billboard projects, building façades and long-distance advertising




Iron-cabinet fixed-installation version with rugged construction for permanent outdoor billboard projects; customized project solutions available.

Model P5	Pixel Pitch 5mm	LED Type SMD1921
Pixel Configuration 1R1G1B	Module Size 320mm×160mm	Module Resolution 64×32 pixels
Cabinet Size 960mm×960mm	Cabinet Resolution 192×192 pixels	Cabinet Material Iron cabinet
Brightness ≥5000CD/m²	Refresh Rate ≥7680Hz	Gray Scale 16 bit
Viewing Angle 140°/140°	Optimal Viewing Distance 5m – 15m	Scan Method 1/8
IP Rating IP65 (outdoor)	Power Consumption 850W/sqm (max) · 350W/sqm (avg)	Cabinet Weight 28 kgs

Pixel Density: 40,000 dots/sqm · Cabinet Thickness: 80mm · Driver IC: FM6373 · Color Temperature: 6,500K · Lifespan: 100,000 hours · Working Voltage: AC 100/240V 50-60Hz · MOQ: 6 sqm · EXW Price: contact for quotation

P5 640X640mm Outdoor

Best for: outdoor advertising, billboards, commercial façades and large-format screens



P5 outdoor screen with compact 640×640mm die-cast cabinets, high brightness and IP65 protection — ideal for outdoor advertising, billboards and commercial façades where flexible assembly is needed.

Model P5	Pixel Pitch 5mm	LED Type SMD1921
Pixel Configuration 1R1G1B	Module Size 320mm×160mm	Module Resolution 64×32 pixels
Cabinet Size 640mm×640mm	Cabinet Resolution 128×128 pixels	Cabinet Material Die-cast aluminum
Brightness ≥5500CD/m²	Refresh Rate ≥7680Hz	Gray Scale 16 bit
Viewing Angle 140°/140°	Optimal Viewing Distance 5m – 50m	Scan Method 1/8
IP Rating IP65 (outdoor)	Power Consumption 850W/sqm (max) · 350W/sqm (avg)	Cabinet Weight 20 kgs

Pixel Density: 40,000 dots/sqm · Cabinet Thickness: 80mm · Driver IC: FM6373 · Color Temperature: 6,500K · Lifespan: 100,000 hours · Working Voltage: AC 100/240V 50-60Hz · MOQ: 6 sqm · EXW Price: contact for quotation

P8 960X960mm Outdoor

Best for: outdoor billboards, highways, building façades and long-distance advertising



P8 outdoor screen with large 960×960mm cabinets for fewer seams; ≥5500CD/m² brightness and IP65 protection for clear long-distance visibility on highways, roads and building façades.

Model P8	Pixel Pitch 8mm	LED Type SMD2727
Pixel Configuration 1R1G1B	Module Size 256mm×128mm	Module Resolution 32×16 pixels
Cabinet Size 960mm×960mm	Cabinet Resolution 120×120 pixels	Cabinet Material Die-cast aluminum
Brightness ≥5500CD/m²	Refresh Rate ≥7680Hz	Gray Scale 16 bit
Viewing Angle 140°/140°	Optimal Viewing Distance 8m – 80m	Scan Method 1/4
IP Rating IP65 (outdoor)	Power Consumption 850W/sqm (max) · 350W/sqm (avg)	Cabinet Weight 28 kgs

Pixel Density: 15,625 dots/sqm · Cabinet Thickness: 80mm · Driver IC: FM6373 · Color Temperature: 6,500K · Lifespan: 100,000 hours · Working Voltage: AC 100/240V 50-60Hz · MOQ: 6 sqm · EXW Price: contact for quotation

P10 960X960mm Outdoor

Best for: outdoor billboards, highways, stadiums and very-long-distance advertising



P10 outdoor screen with large 960×960mm cabinets, ≥6500CD/m² high brightness and IP65 protection — a cost-effective choice for very-long-distance advertising: highways, stadiums and large billboards.

Model P10	Pixel Pitch 10mm	LED Type SMD3535
Pixel Configuration 1R1G1B	Module Size 320mm×160mm	Module Resolution 32×16 pixels
Cabinet Size 960mm×960mm	Cabinet Resolution 96×96 pixels	Cabinet Material Die-cast aluminum
Brightness ≥6500CD/m²	Refresh Rate ≥7680Hz	Gray Scale 16 bit
Viewing Angle 140°/140°	Optimal Viewing Distance 10m – 100m	Scan Method 1/4
IP Rating IP65 (outdoor)	Power Consumption 850W/sqm (max) · 350W/sqm (avg)	Cabinet Weight 28 kgs

Pixel Density: 10,000 dots/sqm · Cabinet Thickness: 80mm · Driver IC: FM6373 · Color Temperature: 6,500K · Lifespan: 100,000 hours · Working Voltage: AC 100/240V 50-60Hz · MOQ: 6 sqm · EXW Price: contact for quotation

PRODUCT LINE

LED Poster Display

High-definition vertical advertising screen for interiors — shops, malls and digital signage.

P2.5 640X1920mm Indoor LED Poster Display ()

P2.5 640X1920mm Indoor LED Poster Display ()

Best for: retail stores, shopping malls, exhibitions and indoor digital advertising



P2.5 indoor LED poster (vertical advertising screen) in the standard 640×1920mm format, with standalone USB / wireless mobile playback and multi-screen cascading; size, brightness and playback system can be customized to client requirements.

Model P2.5	Pixel Pitch 2.5mm	LED Type SMD1515
Pixel Configuration 1R1G1B	Module Size 320mm×160mm	Module Resolution 128×64 pixels
Cabinet Size 640mm×1920mm	Cabinet Resolution 256×768 pixels	Cabinet Material Die-cast aluminum
Brightness ≥1000CD/m²	Refresh Rate ≥7680Hz	Gray Scale 16 bit
Viewing Angle 140°/140°	Optimal Viewing Distance 2.5m – 8m	Scan Method 1/32
IP Rating IP45 (indoor)	Power Consumption 850W/sqm (max) · 350W/sqm (avg)	Cabinet Weight 32 kgs

Pixel Density: 160,000 dots/sqm · Cabinet Thickness: 80mm · Driver IC: FM6373 · Color Temperature: 6,500K · Lifespan: 100,000 hours · Working Voltage: AC 100/240V 50-60Hz · MOQ: 1 piece · EXW Price: contact for quotation

From Inquiry to Delivery

- 1 Send project details**
Screen width × height, indoor/outdoor, viewing distance and destination country.
- 2 Get LED display solution**
We recommend pixel pitch, cabinet size, control system and installation direction.
- 3 Confirm quotation**
Confirm EXW/FOB price, cabinet quantity, spare parts, payment terms and lead time.
- 4 Production & aging test**
Modules, cabinets and complete screens are tested before packing.
- 5 Packing & shipping**
Export wooden cases or flight cases protect the screens in transit.
- 6 Remote technical support**
Cabinet layout, wiring guidance, software setup and after-sales service.

OEM / ODM

Cabinet size, pixel pitch, logo, packaging, product configuration and complete project solutions can be customized to your requirements.

Get a fast quotation

WhatsApp: +86 155 7321 7152

Email: bluestarledfrank@gmail.com

Address: Shenzhen, China

www.bluestaroptolimited.com